




“*” Pivot Dimension

ROHS Component

PO(X)	电流强度 (A)	φA	PCB φB
1	10	1.7	2.0
2	20	2.75	3.05
3	30	3.3	3.6
4	40	3.8	4.10



PCB LAYOUT

MATERIALS AND FINISH

TERMINALS: COPPER ALLOY, ELECTROPLATED NICKEL BASE, 1U"-30U" GOLD PLATING IN CONTACT AREA, TINNED OR TIN-LEAD OR GOLD PLATING IN WELDING AREA, THE MATERIAL USED FOR THE HIGH CURRENT TERMINAL IS PHOSPHORUS COPPER, MALE BRASS; 5A SMALL TERMINAL MATERIAL FEMALE END (CROWN SPRING), MALE END IS BRASS. CLAMP RING: THE MATERIAL USED IS C17200.

THE RUBBER CORE OF RF COAXIAL TERMINAL IS MADE OF TEFLON MATERIAL.

OTHER: RIVET: BRASS, NICKEL-PLATED TIN PLATING OR ON REQUEST;

FORK: BRASS, TINNED/TINNED LEAD/NICKEL TINNED OR AVAILABLE ON REQUEST;

SCREW: BRASS, NICKEL-PLATED TIN ON REQUEST;

SHELL: STEEL OR COPPER ALLOY MATERIAL, Tin/Ni OR Au FINISHED.

CONNECTOR INSULATOR: PBT THERMOPLASTIC, 30% GLASS FILLED, UL 94V-0 RATED.

HIGHT POWER CONTACT : COPPER ALLOY MATERIAL, GOLD PLATED.

ELECTRICAL CHARACTERISTICS

HIGH POWER CONTACT CURRENT RATING: 10, 20, 30 OR 40 AMPS.

THE WORKING VOLTAGE: 300V.

CONTACT IMPEDANCE: SIGNAL TEMINALS: ALL 10MΩ MAX; CURRENT TERMINALS: 2.7MΩ MAX;

DIELECTRIC WITHSTANDING VOLTAGE: 1000 V AC FOR 1 MINUTE.

INSULATION RESISTANCE: 2000 MEGAOHMS MIN.

TEMPERATURE RATING: -55° ~ +125° .

RF TERMINAL CHARACTERISTIC IMPEDANCE: 50Ω ± 5Ω; 75Ω ± 5Ω

WITHSTAND VOLTAGE OF THE RF TERMINAL: 750V AC RMS (STANDARD DEVIATION). AT 1 MINUTE

RF TERMINAL CONTACT IMPEDANCE: 30Ω MAX

RATED VOLTAGE OF THE RF TERMINAL: 250V AC



东莞市迅颢原精密连接器有限公司

Dongguan Signalorigin Precision Connector Co., Ltd

TOLERANCE: X. ±0.38 X.X ±0.25 X.XX ±0.13 X.* ±5° X.X* ±2°	DRAWN BY :	DATE :	PART NAME:	
	杨剑玉	2010. 05. 15	2V2 公 电流弯焊板式铆10.8支架	
 UNIT: mm [inch] SCALE: 1:1 SIZE: A4	CHECKED BY:	DATE :	PART NO.	XHY-05-0219
	侯应文	2010. 05. 15	MOLD NO.	PR02V2MXH0900000000000
	APPROVED BY:	DATE :	REMARK	
	胡超	2010. 05. 15	DRAW NO.	