






“*” Pivot Dimension

ROHS Component

PO(X)	电流强度(A)	φA	PCB φB
1	10	1.7	2.0
2	20	2.75	3.05
3	30	3.3	3.6
4	40	3.8	4.10



PCB LAYOUT



MATERIALS AND FINISH

TERMINALS: COPPER ALLOY, ELECTROPLATED NICKEL BASE, 1U"-30U" GOLD PLATING IN CONTACT AREA, TINNED OR TIN-LEAD OR GOLD PLATING IN WELDING AREA, THE MATERIAL USED FOR THE HIGH CURRENT TERMINAL IS PHOSPHORUS COPPER, MALE BRASS; 5A SMALL TERMINAL MATERIAL FEMALE END (CROWN SPRING), MALE END IS BRASS. CLAMP RING: THE MATERIAL USED IS C17200.

THE RUBBER CORE OF RF COAXIAL TERMINAL IS MADE OF TEFLON MATERIAL.

OTHER: RIVET: BRASS, NICKEL-PLATED TIN PLATING OR ON REQUEST;

FORK: BRASS, TINNED/TINNED LEAD/NICKEL TINNED OR AVAILABLE ON REQUEST;

SCREW: BRASS, NICKEL-PLATED TIN ON REQUEST;

SHELL: STEEL OR COPPER ALLOY MATERIAL, Tin/Ni OR Au FINISHED.

CONNECTOR INSULATOR: PBT THERMOPLASTIC, 30% GLASS FILLED, UL 94V-0 RATED.

HIGH POWER CONTACT: COPPER ALLOY MATERIAL, GOLD PLATED.

ELECTRICAL CHARACTERISTICS

HIGH POWER CONTACT CURRENT RATING: 10, 20, 30 OR 40 AMPS.

THE WORKING VOLTAGE: 300V.

CONTACT IMPEDANCE: SIGNAL TERMINALS: ALL 10MΩ MAX; CURRENT TERMINALS: 2.7MΩ MAX;

DIELECTRIC WITHSTANDING VOLTAGE: 1000 V AC FOR 1 MINUTE.

INSULATION RESISTANCE: 2000 MEGAOHMS MIN.

TEMPERATURE RATING: -55° ~ +125°.

RF TERMINAL CHARACTERISTIC IMPEDANCE: 50Ω ± 5Ω; 75Ω ± 5Ω

WITHSTAND VOLTAGE OF THE RF TERMINAL: 750V AC RMS (STANDARD DEVIATION).

AT 1 MINUTE

RF TERMINAL CONTACT IMPEDANCE: 30Ω MAX

RATED VOLTAGE OF THE RF TERMINAL: 250V AC



东莞市迅颢原精密连接器有限公司

Dongguan Signalorigin Precision Connector Co., Ltd

TOLERANCE: X ±0.38 X.X ±0.25 X.XX ±0.13 X° ±5° X' ±2°		DRAWN BY : 杨剑玉	DATE : 2010.05.15	PART NAME: 2W2 母 电流直焊板式传统铆合	
 UNIT: mm [inch]		CHECKED BY: 侯应文	DATE : 2010.05.15	PART NO. XHY-05-0410	
				MOLD NO. PS02W2FX.000000000000	
		APPROVED BY: 胡超	DATE : 2010.05.15	REMARK	
SCALE:1:1	SIZE: A4			DRAW NO.	